


## Bare Board Loader

**For loading of bare PCB onto production line**


### Features

- Suitable for SMT, ICT Auto and Manual Insertion lines
- Choice of LCD Touch Screen or Push-Button Panel
- Programmable Logic Control
- Front loading of bare boards
- Small footprint
- Pass through mode as standard for all machine size
- Quick vacuum operation and high suction force
- Suction arms adjustable without tools
- High PCB loading capacity
- SMEMA Interface for communication between machines
- Available in other conveying mediums  
e.g. Flat belt, Polycord



### **Bare Board Loader Dimensions (mm)/Weight (approximate in kg)**

	A	B	C	D	W	Weight*
( M ) series	700	1300	500	160	50 to 350	120
( L ) series	850	1300	650	160	50 to 510	150



### **Machine Specification**

Cycle time	10 secs
Capacity	280 pcs 1.0mm thick PCB 930 pcs 0.3mm thick PCB
Reference side	Front or rear as specified
Air requirement	6 to 8 bar / 170 liter /min
Electrical requirement	230VA max (voltage as specified)
Optional Items	Tower light Push-Button / Touch Screen Panel Other sizes available

#### **Note:**

The machine comes with 3 pcs for M size and 4 pcs for L size suction cups of sizes Ø 10mm. Other sizes are available on request.

