




Traverser


For multi-lines traffic diverting of PCBs

Features

- Suitable for SMT, ICT Auto and Manual Insertion lines
- Able to handle multi-lines set up
- Traversed distance up to 4.5m possible
- Choice of LCD Touch Screen or Push-Button Panel
- Programmable Logic Control
- Configurable through the Operator Panel
- SMEMA Interface for communication between machines
- Multi-positioning and high speed possible
- 180° turning unit on shuttle available
- Available in other conveying mediums e.g. Flatbelt, Polycord









Traverser dimensions (mm)/Weight (approximate in kg)						
	A	В	C	D	W	Weight
(M) series	*	1300	500	160*	50 to 350	*
(L) series	*	1300	650	160*	50 to 510	*

^{*} depends on the traversed distance and design

Machine Specification

Cycle time Depending on the traversed distance and design

Reference side Front or rear as specified

Air requirement Depending on the traversed distance and design Depending on the traversed distance and design

Optional Items Tower lights/Buzzer

Push-Button Panel / Touch Screen Panel

Other sizes available

Multi-positioning and high speed possible

Absolute Tech System (Thailand) Co Ltd 75/22 Moo 11, Phaholyothin Road, Klong Nueng, Klong Luang, Pathumthani 12120 Thailand Tel. 02 529 5629 Fax: 02 529 5628